Used Boon Edam Optical Turnstiles

We have two Boon Edam turnstile packages for sale. All components are in excellent working condition and are just over one year old.

Both packages come with:
- HID proximity card readers already installed in each turnstile
- Each turnstile comes with a floor platform with wire channels

Speedlane Slide Package – Consists of 4 cabinets to create 3 lanes of passage, plus a service gate controlled by your reception desk.
- 2 standard Speedlane Slide turnstiles
- 1 ADA Speedlane Slide turnstile
- ADA Swinging Side service gate (Model THG-42)
- Floor platform with wire channels (27 linear feet) – the platform prevents damage to your floor by allowing installation of the turnstiles without drilling into the floor.
- Filler Rail 6.85 ft sections of Stainless Steel with Lexan Panels & Glass Clamps
- External Control Panel

- Weight = 250 lbs per cabinet (1,000 lbs)
- Platform = 150 lbs per platform ()
- Gate = 150 lbs

- Original Cost: $86,000
- Price: $54,000.00
- Shipping from zip code 46032 – freight is not included
- Available to ship after 08/01/2019

Speedlane Swing ADA Package – Consists of 2 cabinets to create 1 lane of passage.
- 1 ADA Speendlane Swing turnstile
- Floor platform with wire channels (5 linear feet)
- Filler Rail 6" sections of Stainless Steel with Lexan Panels & Glass Clamps

- Speedlane Swings = 200 lbs per cabinet (400 lbs)
- Platform = 150 lbs per piece

- Original Price: $25,000
- Price: $10,000
- Shipping from 46032 – freight is not included
- Available to ship after 08/01/2019

Lifeline Speedlane Slide Specifications

Diameter / Unit Width (inches)	12-1/4" (ADA: 20-1/8")
Barrier Height (inches)	38-9/16"
Capacity (per minute)	25-30
Security Level (0 - 5)	Security-level-3
# of Door Wings	2 per lane
Disabled Access	Yes
Fail Safe / Fail Secure	Yes/Yes
Collapsible Door Set or Barrier	No
Finish	Stainless Steel with Black Glass Top
Options	Barrier Free Mode*
	External Control Panel
	Jump Over Detection Sensors
Power Supply	110-240 VAC, 50/60 Hz
Power Consumption (Operating)	80W
Power Consumption (Stationary)	60W
Power Consumption (Sleep mode)	40W
Ambient Temperature	5°F to +122°F
Weight	727 lbs-
Product Link	https://www.boonedam.us/product/security-access/optical-turnstile/speedlane-slide

Lifeline Speedlane Swing Specifications

Diameter / Unit Width (inches)	4-1/8"
Barrier Height (inches)	37"
Capacity (per minute)	25-30
Security Level (0 - 5)	Security-level-3
# of Door Wings	2 per lane
Disabled Access	Yes
Fail Safe / Fail Secure	Yes/No
Collapsible Door Set or Barrier	No
Finish	Stainless Steel with Black Glass Top
Options	External Control Panel
	Remote Monitoring
Power Supply	110-240 VAC, 50/60 Hz
Power Consumption (Operating)	80W
Power Consumption (Stationary)	60W
Power Consumption (Sleep mode)	40W
Ambient Temperature	5°F to +122°F
Weight	440 lbs
Product Link	https://www.boonedam.us/product/security-access/optical-turnstile/speedlane-swing